

SPECIFICATIONS

TRIUMPH

STREET TRIPLE R



STREET TRIPLE R
Matte Graphite



STREET TRIPLE R
Matte Blazing Orange

ENGINE AND TRANSMISSION:

Type	Liquid-cooled, 12 valve, DOHC, in-line 3-cylinder
Capacity	675cc
Bore/Stroke	74.0 x 52.3mm
Fuel System	Multipoint sequential electronic fuel injection with SAI
Final Drive	O ring chain
Clutch	Wet, multi-plate
Gearbox	6-speed, close ratio

CHASSIS, RUNNING GEAR AND DISPLAYS:

Frame	Aluminium beam twin-spar
Swingarm	Braced, twin-sided, cast aluminium alloy
Wheels	Front: Cast aluminium alloy 5-spoke 17 x 3.5in Rear: Cast aluminium alloy 5-spoke 17 x 5.5in
Tires	Front: 120/70 ZR 17 Rear: 180/55 ZR 17
Suspension	Front: Kayaba 41mm upside down forks with adjustable preload, rebound and compression damping, 120mm travel Rear: Kayaba monoshock with piggy back reservoir adjustable for preload, rebound and compression damping, 130mm rear wheel travel
Brakes	Front: Twin 308mm floating discs. Nissin 4-piston radial calipers Rear: Single 220mm disc, Nissin single piston caliper
Front brake master cylinder	Nissin radial master cylinder 19mm diameter
Instrument display/functions	LCD multi-functional speedometer, trip computer, analogue tachometer, lap timer, gear position indicator and programmable gear change lights

DIMENSIONS AND CAPACITIES:

Length	2030mm (79.9in)
Width (Handlebars)	731mm (28.8in)
Height	1250mm (49.2in)
Seat Height	805mm (31.6in)
Wheelbase	1390mm (54.7in)
Rake/Trail	23.9°/92.4mm
Dry Weight	167kg (367lbs)
Fuel Tank Capacity	17.4 liters (3.8 gal / 4.6 US gals)

PERFORMANCE: (MEASURED AT CRANKSHAFT TO DIN 70020)

Maximum Power	108PS / 107bhp / 79kW @ 11700rpm
Maximum Torque	69Nm / 51ft.lbf @ 9100rpm